

MAXAttach™

Expandable Tabletop Conference Phones

The industry's first fully expandable tabletop conference phones. MAXAttach comes with two complete phone units and provides premium, full-duplex audio in medium sized rooms. It also features the ability to link up to two additional phone units for unrivaled microphone and loudspeaker coverage in larger rooms.

ClearOne®



UNRIVALED AUDIO
QUALITY, FLEXIBILITY
AND AFFORDABILITY

MAXATTACH APPLICATIONS

- Executive Office
- Medium Conference Room
- Large Conference Room
- Training Room
- Separate Rooms

MAXATTACH ADVANTAGES

Superior Audio Performance

- + Distributed Echo Cancellation® effectively eliminates echo
- + Noise cancellation removes background noises from fans or HVAC systems
- + Full-duplex sound enables participants to speak and listen at the same time without cutting in and out
- + Automatic level controls keep participants' audio balanced and consistent
- + First-mic priority eliminates hollow "tunnel" sound by activating only the microphone closest to the person speaking
- + Three microphones in each phone unit provide 360° audio pickup

Expandability

MAXAttach

- + Comes with two phone units and a single base unit for medium conference rooms; also available in 3-phone and 4-phone kits
- + Link up to four complete phones, not just microphones, for expanded coverage with MAX EX Expansion Kits
- + Divide MAXAttach into multiple phone systems for use in separate rooms with MAX EX Expansion Base

MAX EX Expansion Kit

- + Includes phone and connecting cable to expand MAXAttach room coverage (base not included)

MAX EX Expansion Base

- + Used to divide MAXAttach into multiple phone systems for use in separate rooms to provide unrivaled flexibility and affordability

Ease of Use & Control


- + Simply plug base unit into power and phone line, connect the phones, then dial and talk
- + Features user-friendly telephone style controls
- + Speed dial stores 10 frequently dialed numbers
- + Recording output on base unit connects to a recording device to capture both sides of the conversation
- + Linked MAX phones can be operated using the dial pad of any phone – dialing, mute, volume controls, etc.

> ROOM APPLICATIONS

MAX EX



MAXAttach™ (MAX EX + MAX Exp. Kit)




MAX EX Expansion Kit

Use with any MAX Phone to expand coverage up to 4 total units.


MAXAttach + 1 Exp. Kit



MAXAttach + 2 Exp. Kits



MAX EX Expansion Base



Enables MAXAttach and MAX EX Expansion Kits to be used in separate rooms. Includes power supply and 25' cable.

> SPECIFICATIONS

Echo Cancellation

Tail time: 60 ms x 3

Noise Cancellation

Dynamic noise cancellation

Telephone Connection

Analog PBX or PSTN line
RJ-11C, -12 dBm nominal

Keypad

Alphanumeric standard keypad

Loudspeaker

Volume: 90dBspl A weighted @ 1 ft
Bandwidth: 200 Hz–3.3 kHz

Record Output

Connector: 2.5 mm mono audio jack
Impedance: <1000 ohms
Bandwidth: 200 Hz–3.3 kHz
Dynamic range: 60 dB
THD <.01%

Certifications

FCC part 15 Class A
FCC part 68
UL Certified

Power

Base unit:
Auto-adjusting power module;
100-240 VAC; 50/60 Hz

Environmental

Operating temperature: 32–118° F
(0–48° C)
Storage temperature: 41–158° F
(5–70° C)
Operating humidity: 15 to 80%
Storage humidity: 10 to 90%

Dimensions (W x D x H)

Phone unit: 10.5" x 10.5" x 3"
(26.7 cm x 26.7 cm x 7.6 cm)
Base unit: 4.25" x 5.5" x 2.5"
(10.8 cm x 14 cm x 6.4 cm)

Weight

Phone unit: 2.7 lb (1.2 kg)
Base unit: .6 lb (0.27 kg)
Shipping: 10 lb (4.5 kg)

PART NUMBERS

MAXAttach*

910-158-500-00 (North America)
910-158-501-00 (Europe/UK - ROHS)
* For MAXAttach plus 1, change -00 to -01 in part number; for MAXAttach plus 2, change -00 to -02 in part number.
910-158-058 (Hong Kong/Singapore)
910-158-056 (Japan)
910-158-059 (Australia/New Zealand)
910-158-060 (South Africa)
910-158-061 (South Korea)
910-158-062 (China)

* For MAXAttach plus 1, add -01 to part number; for MAXAttach plus 2, add -02 to part number.

Includes:
MAX phone units (2)
MAX base unit (1)
12' Cat. 5 cable (1)
25' Cat. 5 cable (1)
Telephone cable
Documentation CD
Quick start guide

MAX EX Expansion Kit

910-158-555 (All countries)

Includes:
MAX phone unit (1)
12' Cat. 5 cable (1)
Documentation CD
Quick start guide

MAX EX Expansion Base

910-158-551 (Europe/UK - ROHS)
910-158-550 (All other countries)

Includes:
MAX base unit (1)
25' Cat. 5 cable (1)
Telephone cable
Documentation CD
Quick start guide



> CLEARONE LOCATIONS

Headquarters:

Salt Lake City, UT USA
5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116
Tel: 801-975-7200
800-945-7730
Fax: 801-977-0087
sales@clearone.com

Latin America

Tel: 801-974-3621
global@clearone.com

EMEA

Tel: 44 (0) 1189 036 053
global@clearone.com

APAC

Tel: 801-303-3388
global@clearone.com