

### Overview

### HPE 1410 Switch series

#### Models

HP 1410-8G Switch	J9559A
HP 1410-16G Switch	J9560A
HP 1410-24G-R Switch	JG708A
HP 1410-24G Switch	J9561A
HP 1410-8 Switch	J9661A
HP 1410-16 Switch	J9662A
HP 1410-24 Switch	J9663A
HP 1410-24-R Switch	JD986B
HP 1410-24-2G Switch	J9664A

#### Key features

- Unmanaged Gigabit Ethernet and Fast Ethernet switches
- Green features for low power consumption
- Fan-less design for silent operation
- QoS support
- Limited Lifetime warranty

#### Product overview

The HPE 1410 Switch Series comprises unmanaged Gigabit Ethernet and Fast Ethernet switches, designed for small businesses looking for entry-level low-cost networking solutions that come with a limited lifetime warranty. The series consists of nine models with flexible mounting options to meet different network switching needs. All models have quality of service (QoS) support and IEEE 802.3x flow control features that provide outstanding data efficiency.

Simplified plug-and-play convenience is enabled by features such as auto-MDIX and autospeed negotiation. Hewlett Packard Enterprise has innovated and combined the latest advances in silicon technology to bring you some of the most power-efficient switches—1410-24G-R, 1410-16, and 1410-24 models are advanced IEEE 802.3az-compliant unmanaged Gigabit and Fast Ethernet switches. The switches come with built-in green features and a limited lifetime warranty, making the series the right choice for organizations seeking a networking solution that's both economical and reliable.

#### Features and benefits

##### Quality of Service (QoS)

- **IEEE 802.1p prioritization**  
delivers data to devices based on the priority and type of traffic
- **DiffServ Code Point (DSCP) support**  
allows real-time traffic prioritization based on Layer 3 TOS/DSCP parameters

#### Connectivity



## Overview

- **Auto-MDIX**  
provides automatic adjustments for straight-through or crossover cables on all 10/100 and 10/100/1000 ports

## Performance

- **NEW Energy-efficient Ethernet support**  
supports new IEEE 802.3az standard; allows lower power consumption when operated with IEEE-compliant client devices in 100 Mb/s mode only (JG708A, J9662A and J9663A switches)
- **Half-/full-duplex auto-negotiating capability on every port**  
doubles the throughput of every port
- **NEW Jumbo frame support**  
allows frames up to 9216 bytes to be switched through the network (Gigabit Ethernet models)
- **Mini jumbo frame support**  
allows frames up to 2048 bytes to be switched through the network, which supports large data transfers (J9662A and J9663A switches)

## Ease of use

- **Unmanaged**  
provides plug-and-play simplicity
- **Comprehensive LED display with per-port indicators**  
provides an at-a-glance view of status, activity, speed and full-duplex operation
- **Flow control**  
helps ensure reliable communications during full-duplex operation
- **Auto-speed negotiation**  
selects individual port speed automatically depending on client capabilities without the need for manual intervention, allowing for simple plug-and-play operation

## Flexibility

- **Fanless design**  
enables quiet operation for deployment in open spaces
- **Internal power supply**  
provides operation convenience and a neat operation environment (JG708A, J9561A and JD986B switches)

## Warranty and support

- **Limited Lifetime Warranty v2.0**  
See <http://www.hpe.com/networking/warrantysummary> for warranty and support information included with your product purchase.

## Configuration

**Build To Order:** BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

HP 1410-8G Switch <ul style="list-style-type: none"> <li>• 8 autosensing 10/100/1000 ports</li> </ul>	J9559A See Configuration <b>NOTE:2</b>
HP 1410-16G Switch <ul style="list-style-type: none"> <li>• 16 autosensing 10/100/1000 ports</li> <li>• 1U - Height</li> </ul>	J9560A See Configuration <b>NOTE:2</b>
HP 1410-24G-R Switch <ul style="list-style-type: none"> <li>• 24 autosensing 10/100/1000 ports</li> <li>• 1U - Height</li> </ul>	JG708A See Configuration <b>NOTE:2</b>
HP 1410-24G Switch <ul style="list-style-type: none"> <li>• 22 autosensing 10/100/1000 ports</li> <li>• 2 dual-personality ports; either an RJ-45 10/100/1000 port or an open mini-GBIC slot</li> <li>• 1U - Height</li> </ul>	J9561A See Configuration <b>NOTE:1, 3</b>
PDU Cable NA/MX/TW/JP <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (NA/MX/TW/JP)</li> </ul>	J9561A #B2B
PDU Cable ROW <ul style="list-style-type: none"> <li>• C15 PDU Jumper Cord (ROW)</li> </ul>	J9561A #B2C
HP 1410-8 Switch <ul style="list-style-type: none"> <li>• 8 autosensing 10/100 ports</li> </ul>	J9661A See Configuration <b>NOTE:2</b>
HP 1410-16 Switch <ul style="list-style-type: none"> <li>• 16 autosensing 10/100 ports</li> <li>• 1U - Height</li> </ul>	J9662A See Configuration <b>NOTE:2</b>
HP 1410-24 Switch <ul style="list-style-type: none"> <li>• 24 autosensing 10/100 ports</li> <li>• 1U - Height</li> </ul>	J9663A See Configuration <b>NOTE:2</b>

## Configuration

### HP 1410-24-R Switch

- 24 autosensing 10/100 ports
- 1U - Height

JD986B

See Configuration

**NOTE:2**

### HP 1410-24-2G Switch

- 24 autosensing 10/100ports
- 2 autosensing 10/100/1000 ports
- 1U - Height

J9664A

See Configuration

**NOTE:2**

### Configuration Rules:

Note 1	The following Transceivers install into this switch: HP X121 1G SFP LC SX Transceiver HP X121 1G SFP LC LX Transceiver HP X111 100M SFP LC FX Transceiver	J4858C J4859C J9054C
Note 2	Localization required. (See Localization Menu for list.)	
Note 3	Localization (Wall Power Cord) required on orders without #B2B or #B2C (PDU Power Cord). (See Localization Menu)	

## Internal or External Power Supplies(Model Dependant)

Power supplies included

**Enter the following menu selections as integrated to the CTO Model X server above if order is factory built.**

## Transceivers

### SFP Transceivers

HP X121 1G SFP LC SX Transceiver	J4858C
HP X121 1G SFP LC LX Transceiver	J4859C
HP X111 100M SFP LC FX Transceiver	J9054C

## Cables

### Multi-Mode Cables

HP LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable	AJ833A
HP LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable	AJ834A
HP LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable	AJ835A

## Configuration

HP LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
HP LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
HP LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
HP LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A

## Technical Specifications

### HP 1410-8G Switch (J9559A)

<b>I/O ports and slots</b>	8 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) Media Type: Auto-MDIX Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only														
	Supports a maximum of 8 autosensing 10/100/1000 ports														
<b>Physical characteristics</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Dimensions</b></td> <td>6.14(w) x 3.8(d) x 0.96(h) in (15.6 x 9.65 x 2.45 cm)</td> </tr> <tr> <td style="vertical-align: top;"><b>Weight</b></td> <td>0.74 lb (0.34 kg)</td> </tr> </table>	<b>Dimensions</b>	6.14(w) x 3.8(d) x 0.96(h) in (15.6 x 9.65 x 2.45 cm)	<b>Weight</b>	0.74 lb (0.34 kg)										
<b>Dimensions</b>	6.14(w) x 3.8(d) x 0.96(h) in (15.6 x 9.65 x 2.45 cm)														
<b>Weight</b>	0.74 lb (0.34 kg)														
<b>Memory and processor</b>	4 Kb EEPROM capacity; packet buffer size: 192 KB														
<b>Mounting and enclosure</b>	Wall, desktop, and under-table mounting														
<b>Performance</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>100 Mb Latency</b></td> <td>&lt; 3.6 <math>\mu</math>s (LIFO 64-byte packets)</td> </tr> <tr> <td style="vertical-align: top;"><b>1000 Mb Latency</b></td> <td>&lt; 1.2 <math>\mu</math>s (LIFO 64-byte packets)</td> </tr> <tr> <td style="vertical-align: top;"><b>Throughput</b></td> <td>up to 11.9 Mpps (64-byte packets)</td> </tr> <tr> <td style="vertical-align: top;"><b>Switching capacity</b></td> <td>16 Gbps</td> </tr> <tr> <td style="vertical-align: top;"><b>MAC address table size</b></td> <td>4096 entries</td> </tr> </table>	<b>100 Mb Latency</b>	< 3.6 $\mu$ s (LIFO 64-byte packets)	<b>1000 Mb Latency</b>	< 1.2 $\mu$ s (LIFO 64-byte packets)	<b>Throughput</b>	up to 11.9 Mpps (64-byte packets)	<b>Switching capacity</b>	16 Gbps	<b>MAC address table size</b>	4096 entries				
<b>100 Mb Latency</b>	< 3.6 $\mu$ s (LIFO 64-byte packets)														
<b>1000 Mb Latency</b>	< 1.2 $\mu$ s (LIFO 64-byte packets)														
<b>Throughput</b>	up to 11.9 Mpps (64-byte packets)														
<b>Switching capacity</b>	16 Gbps														
<b>MAC address table size</b>	4096 entries														
<b>Environment</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Operating temperature</b></td> <td>32°F to 104°F (0°C to 40°C)</td> </tr> <tr> <td style="vertical-align: top;"><b>Operating relative humidity</b></td> <td>15% to 95% @ 104°F (40°C), noncondensing</td> </tr> <tr> <td style="vertical-align: top;"><b>Nonoperating/Storage temperature</b></td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td style="vertical-align: top;"><b>Nonoperating/Storage relative humidity</b></td> <td>15% to 90% @ 149°F (65°C), noncondensing</td> </tr> <tr> <td style="vertical-align: top;"><b>Altitude</b></td> <td>up to 10,000 ft. (3 km)</td> </tr> <tr> <td style="vertical-align: top;"><b>Acoustic</b></td> <td>Power: 0 dB No fan</td> </tr> </table>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)	<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C), noncondensing	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)	<b>Nonoperating/Storage relative humidity</b>	15% to 90% @ 149°F (65°C), noncondensing	<b>Altitude</b>	up to 10,000 ft. (3 km)	<b>Acoustic</b>	Power: 0 dB No fan		
<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)														
<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C), noncondensing														
<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)														
<b>Nonoperating/Storage relative humidity</b>	15% to 90% @ 149°F (65°C), noncondensing														
<b>Altitude</b>	up to 10,000 ft. (3 km)														
<b>Acoustic</b>	Power: 0 dB No fan														
<b>Electrical characteristics</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Frequency</b></td> <td>50/60 Hz</td> </tr> <tr> <td style="vertical-align: top;"><b>Maximum heat dissipation</b></td> <td>41 BTU/hr (43.26 kJ/hr)</td> </tr> <tr> <td style="vertical-align: top;"><b>Voltage</b></td> <td>100 - 240 VAC, rated (depending on power supply chosen)</td> </tr> <tr> <td style="vertical-align: top;"><b>Current</b></td> <td>1.0 A</td> </tr> <tr> <td style="vertical-align: top;"><b>Maximum power rating</b></td> <td>12 W</td> </tr> <tr> <td style="vertical-align: top;"><b>Notes</b></td> <td>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</td> </tr> <tr> <td></td> <td>The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.</td> </tr> </table>	<b>Frequency</b>	50/60 Hz	<b>Maximum heat dissipation</b>	41 BTU/hr (43.26 kJ/hr)	<b>Voltage</b>	100 - 240 VAC, rated (depending on power supply chosen)	<b>Current</b>	1.0 A	<b>Maximum power rating</b>	12 W	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.		The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.
<b>Frequency</b>	50/60 Hz														
<b>Maximum heat dissipation</b>	41 BTU/hr (43.26 kJ/hr)														
<b>Voltage</b>	100 - 240 VAC, rated (depending on power supply chosen)														
<b>Current</b>	1.0 A														
<b>Maximum power rating</b>	12 W														
<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.														
	The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.														
<b>Safety</b>	CSA 22.2 No. 60950; EN 60950/IEC 60950; UL 60950-1														
<b>Emissions</b>	FCC Rules Part 15, Subpart B Class A														

## Technical Specifications

<b>Immunity</b>	<b>Generic</b>	EN 55022 CISPR 22
	<b>EN</b>	EN 55024, CISPR 24
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	

### HP 1410-16G Switch (J9560A)

<b>I/O ports and slots</b>	16 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) Media Type: Auto-MDIX Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	Supports a maximum of 16 autosensing 10/100/1000 ports	
<b>Physical characteristics</b>	<b>Dimensions</b>	8.21(w) x 4.41(d) x 1.73(h) in (20.85 x 11.2 x 4.4 cm) (1U height)
	<b>Weight</b>	1.43 lb (0.65 kg)
<b>Memory and processor</b>	512 Kb flash; packet buffer size: 512 KB	
<b>Mounting and enclosure</b>	Mounts in an EIA standard 19-inch telco rack (hardware included); wall, desktop and under-table mounting	
<b>Performance</b>	<b>100 Mb Latency</b>	< 8.0 $\mu$ s (LIFO 64-byte packets)
	<b>1000 Mb Latency</b>	< 3.6 $\mu$ s (LIFO 64-byte packets)
	<b>Throughput</b>	up to 23.8 Mpps (64-byte packets)
	<b>Switching capacity</b>	32 Gbps
	<b>MAC address table size</b>	8192 entries
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C), noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	15% to 90% @ 149°F (65°C), noncondensing
	<b>Altitude</b>	up to 10,000 ft. (3 km)
	<b>Acoustic</b>	Power: 0 dB No fan
<b>Electrical characteristics</b>	<b>Frequency</b>	50/60 Hz

## Technical Specifications

<b>Maximum heat dissipation</b>	44 BTU/hr (46.42 kJ/hr)
<b>Voltage</b>	100 - 240 VAC, rated (depending on power supply chosen)
<b>Current</b>	1.1 A
<b>Maximum power rating</b>	13 W
<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.  The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.

**Safety** CSA 22.2 No. 60950; UL 60950-1; IEC 60950-1; EN 60950-1

**Emissions** FCC Rules Part 15, Subpart B Class A

<b>Immunity</b>	<b>Generic</b>	EN 55022 CISPR 22
	<b>EN</b>	EN 55024, CISPR 24
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3

**Services** Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

---

### HP 1410-24G-R Switch (JG708A)

<b>I/O ports and slots</b>	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) Media Type: Auto-MDIX Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only Supports a maximum of 24 autosensing 10/100/1000 ports	
<b>Physical characteristics</b>	<b>Dimensions</b>	17.32(w) x 6.81(d) x 1.73(h) in (44 x 17.3 x 4.4 cm) (1U height)
	<b>Weight</b>	6.61 lb (3 kg)
<b>Memory and processor</b>	1 MB flash; packet buffer size: 512 KB	
<b>Mounting and enclosure</b>	Mounts in an EIA standard 19-inch telco rack (hardware included); desktop mounting	
<b>Performance</b>	<b>100 Mb Latency</b>	< 8.0 $\mu$ s (LIFO 64-byte packets)
	<b>1000 Mb Latency</b>	< 3.6 $\mu$ s (LIFO 64-byte packets)



## Technical Specifications

	<b>Throughput</b>	up to 35.7 Mpps (64-byte packets)
	<b>Switching capacity</b>	48 Gbps
	<b>MAC address table size</b>	8192 entries
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	5% to 95% @ 104°F (40°C), noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	5% to 90% @ 149°F (65°C), noncondensing
	<b>Altitude</b>	up to 16,404 ft (5 km)
	<b>Acoustic</b>	Power: 0 dB No fan
<b>Electrical characteristics</b>	<b>Frequency</b>	50/60 Hz
	<b>Maximum heat dissipation</b>	55 BTU/hr (58 kJ/hr)
	<b>Voltage</b>	100 - 240 VAC, rated (depending on power supply chosen)
	<b>Current</b>	0.3 A
	<b>Maximum power rating</b>	16 W
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.  This model provides internal power supply. Please select the correct power cord country option.
<b>Safety</b>		CSA 22.2 No. 60950; UL 60950-1; IEC 60950-1; EN 60950-1
<b>Emissions</b>		FCC Rules Part 15, Subpart B Class A
<b>Immunity</b>	<b>Generic</b>	EN 55022 CISPR 22
	<b>EN</b>	EN 55024, CISPR 24
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3
<b>Notes</b>		IEEE 802.3az Energy Efficient Ethernet protocol is supported by the HP 1410-24G-R (JG708A), HP 1410-16 (J9662A) and HP 1410-24 (J9663A) Switches.

## Technical Specifications

**Services** Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP 1410-24G Switch (J9561A)

<b>I/O ports and slots</b>	22 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) Media Type: Auto-MDIX Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	2 dual-personality ports each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab 1000BASE-T Gigabit Ethernet) or an open mini-GBIC slot (for use with mini-GBIC transceivers)	
	Supports a maximum of 24 Gigabit Ethernet ports	
<b>Physical characteristics</b>	<b>Dimensions</b>	13.23(w) x 6.65(d) x 1.73(h) in (33.6 x 16.9 x 4.4 cm) (1U height)
	<b>Weight</b>	2.98 lb (1.35 kg)
<b>Memory and processor</b>	512 Kb flash; packet buffer size: 512 KB	
<b>Mounting and enclosure</b>	Mounts in an EIA standard 19-inch telco rack (hardware included); wall, desktop and under-table mounting	
<b>Performance</b>	<b>100 Mb Latency</b>	< 8.0 $\mu$ s (LIFO 64-byte packets)
	<b>1000 Mb Latency</b>	< 3.6 $\mu$ s (LIFO 64-byte packets)
	<b>Throughput</b>	up to 35.7 Kpps (64-byte packets)
	<b>Switching capacity</b>	48 Gbps
	<b>MAC address table size</b>	8192 entries
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C), noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	15% to 90% @ 14.9°F (65°C), noncondensing
	<b>Altitude</b>	up to 10,000 ft (3 km)
	<b>Acoustic</b>	Power: 0 dB No fan
<b>Electrical characteristics</b>	<b>Frequency</b>	50/60 Hz
	<b>Maximum heat dissipation</b>	75 BTU/hr (79.13 kJ/hr)
	<b>Voltage</b>	100 - 127 / 200 - 240 VAC, rated (depending on power supply chosen)
	<b>Current</b>	0.3/0.2 A
	<b>Maximum power rating</b>	22 W
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.&lt;br&gt;This model provides internal power supply. Please select the correct power cord country option.

**Safety** CSA 22.2 No. 60950; UL 60950-1; IEC 60950-1; EN 60950-1

## Technical Specifications

<b>Emissions</b>	FCC Rules Part 15, Subpart B Class A	
<b>Immunity</b>	<b>Generic</b>	EN 55022 CISPR 22
	<b>EN</b>	EN 55024, CISPR 24
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3
<b>Notes</b>	Use only supported genuine HP mini-GBICs with your switch.	
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	

### HP 1410-8 Switch (J9661A)

<b>I/O ports and slots</b>	8 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) Duplex: half or full	
	Supports a maximum of 8 autosensing 10/100 ports	
<b>Physical characteristics</b>	<b>Dimensions</b>	6.14(w) x 3.74(d) x 0.97(h) in (15.6 x 9.5 x 2.46 cm)
	<b>Weight</b>	0.74 lb (0.34 kg)
<b>Memory and processor</b>	16 Kb EEPROM; packet buffer size: 96 KB	
<b>Mounting and enclosure</b>	Wall, desktop and under-table mounting	
<b>Performance</b>	<b>100 Mb Latency</b>	< 3.7µs (LIFO 64-byte packets)
	<b>Throughput</b>	up to 1.1 Mpps (64-byte packets)
	<b>Switching capacity</b>	1.6 Gbps
	<b>MAC address table size</b>	1024 entries
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C), noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	15% to 90% @ 149°F (65°C), noncondensing
	<b>Altitude</b>	up to 10,000 ft (3 km)
	<b>Acoustic</b>	Power: 0 dB No fan
<b>Electrical characteristics</b>	<b>Frequency</b>	50/60 Hz

## Technical Specifications

<b>Maximum heat dissipation</b>	13 BTU/hr (13.72 kJ/hr)
<b>Voltage</b>	100 - 240 VAC, rated (depending on power supply chosen)
<b>Current</b>	0.3 A
<b>Maximum power rating</b>	3.6 W
<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.  The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.

**Safety** UL 60950-1; CSA 22.2 60950-1; IEC 60950-1:2005; EN 60950-1:2006 + A11:2009

**Emissions** FCC Rules Part 15, Subpart B Class A

<b>Immunity</b>	<b>Generic</b>	EN 55022 CISPR 22
	<b>EN</b>	EN 55024, CISPR 24
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3

**Services** Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

---

### HP 1410-16 Switch (J9662A)

<b>Ports</b>	16 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) Duplex: half or full  Supports a maximum of 16 autosensing 10/100 ports
<b>Physical characteristics</b>	<b>Dimensions</b> 8.21(w) x 4.21(d) x 1.73(h) in (20.85 x 10.69 x 4.39 cm) (1U height) <b>Weight</b> 1.43 lb (0.65 kg)
<b>Memory and processor</b>	16 Kb EEPROM; packet buffer size: 2 Mb
<b>Mounting and enclosure</b>	Mounts in an EIA standard 19-inch telco rack (hardware included); wall, desktop and under-table mounting
<b>Performance</b>	<b>100 Mb Latency</b> < 10.6 $\mu$ s (LIFO 64-byte packets)

## Technical Specifications

	<b>Throughput</b>	up to 2.3 Mpps (64-byte packets)
	<b>Switching capacity</b>	3.2 Gbps
	<b>MAC address table size</b>	8192 entries
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C), noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	15% to 90% @ 149°F (65°C), noncondensing
	<b>Altitude</b>	up to 10,000 ft. (3 km)
	<b>Acoustic</b>	Power: 0 dB No fan
<b>Electrical characteristics</b>	<b>Frequency</b>	50/60 Hz
	<b>Maximum heat dissipation</b>	13 BTU/hr (13.72 kJ/hr)
	<b>Voltage</b>	100 - 240 VAC, rated (depending on power supply chosen)
	<b>Current</b>	0.3 A
	<b>Maximum power rating</b>	3.6 W
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated
		The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.
<b>Safety</b>		UL 60950-1; CSA C22.2 60950-1; IEC 60950-1:2005; EN 60950-1:2006 + A11:2009
<b>Emissions</b>		FCC Rules Part 15, Subpart B Class A
<b>Immunity</b>	<b>Generic</b>	EN 55022 CISPR 22
	<b>EN</b>	EN 55024, CISPR 24
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3

## Technical Specifications

<b>Notes</b>	IEEE 802.3az Energy Efficient Ethernet protocol is supported by the HP 1410-24G-R (JG708A), HP 1410-16 (J9662A) and HP 1410-24 (J9663A) Switches.
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP 1410-24 Switch (J9663A)

<b>I/O ports and slots</b>	24 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) Duplex: half or full	
	Supports a maximum of 24 autosensing 10/100 ports	
<b>Physical characteristics</b>	<b>Dimensions</b>	13.23(w) x 6.65(d) x 1.73(h) in (33.6 x 16.89 x 4.39 cm) (1U height)
	<b>Weight</b>	2.98 lb (1.35 kg)
<b>Memory and processor</b>	16 Kb EEPROM; packet buffer size: 2 Mb	
<b>Mounting and enclosure</b>	Mounts in an EIA standard 19-inch telco rack (hardware included); wall, desktop and under-table mounting	
<b>Performance</b>	<b>100 Mb Latency</b>	< 11 $\mu$ s (LIFO 64-byte packets)
	<b>Throughput</b>	up to 3.5 Mpps (64-byte packets)
	<b>Switching capacity</b>	4.8 Gbps
	<b>MAC address table size</b>	8192 entries
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C), noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	15% to 90% @ 14.9°F (65°C), noncondensing
	<b>Altitude</b>	up to 10,000 ft (3 km)
	<b>Acoustic</b>	Power: 0 dB No fan
<b>Electrical characteristics</b>	<b>Frequency</b>	50/60 Hz
	<b>Maximum heat dissipation</b>	17 BTU/hr (17.93 kJ/hr)
	<b>AC Voltage</b>	100 - 240 VAC
	<b>Current</b>	0.4 A
	<b>Maximum power rating</b>	4.8 W
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.
<b>Safety</b>	UL 60950-1; CSA 22.2 60950-1; IEC 60950-1:2005; EN 60950-1:2006 + A11:2009	

## Technical Specifications

<b>Emissions</b>	FCC Rules Part 15, Subpart B Class A	
<b>Immunity</b>	<b>Generic</b>	EN 55022 CISPR 22
	<b>EN</b>	EN 55024, CISPR 24
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2
<b>Flicker</b>	IEC 61000-3-3	
<b>Notes</b>	IEEE 802.3az Energy Efficient Ethernet protocol is supported by the HP 1410-24G-R (JG708A), HP 1410-16 (J9662A) and HP 1410-24 (J9663A) Switches.	
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	

### HP 1410-24-R Switch (JD986B)

<b>I/O ports and slots</b>	24 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) Duplex: half or full	
	Supports a maximum of 24 autosensing 10/100 ports	
<b>Physical characteristics</b>	<b>Dimensions</b>	17.32(w) x 6.81(d) x 1.73(h) in (44 x 17.3 x 4.4 cm)
	<b>Weight</b>	4.41 lb (2.0 kg)
<b>Memory and processor</b>	8kb EEPROM; packet buffer size: 2 Mb	
<b>Mounting and enclosure</b>	Mounts in an EIA standard 19-inch telco rack (hardware included); desktop mounting	
<b>Performance</b>	<b>100 Mb Latency</b>	< 11 $\mu$ s (LIFO 64-byte packets)
	<b>Throughput</b>	up to 3.5 Mpps (64-byte packets)
	<b>Switching capacity</b>	4.8 Gbps
	<b>MAC address table size</b>	8192 entries
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C), noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	5% to 90% @ 149°F (65°C), noncondensing
	<b>Altitude</b>	up to 16,404 ft (5 km)
	<b>Acoustic</b>	Power: 0 dB No fan
<b>Electrical characteristics</b>	<b>Frequency</b>	50/60 Hz

## Technical Specifications

<b>Maximum heat dissipation</b>	21 BTU/hr (22 kJ/hr)
<b>AC Voltage</b>	100 - 240 VAC
<b>Current</b>	1.1 A
<b>Maximum power rating</b>	3.6 W
<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
	This model provides an internal power supply. Please select the correct power cord country option.

**Safety** UL 60950-1; CSA 22.2 60950-1; IEC 60950-1:2005; EN 60950-1:2006 + A11:2009

**Emissions** FCC Rules Part 15, Subpart B Class A

<b>Immunity</b>	<b>Generic</b>	EN 55022 CISPR 22
	<b>EN</b>	EN 55024, CISPR 24
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2
<b>Flicker</b>	IEC 61000-3-3	

**Services** Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

---

### HP 1410-24-2G Switch (J9664A)

<b>I/O ports and slots</b>	24 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) Duplex: half or full 2 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only Supports a maximum of 24 autosensing 10/100 ports plus 2 autosensing 10/100/1000 ports	
<b>Physical characteristics</b>	<b>Dimensions</b>	13.23(w) x 6.65(d) x 1.73(h) in (33.6 x 16.89 x 4.39 cm) (1U height)
	<b>Weight</b>	2.98 lb (1.35 kg)
<b>Memory and processor</b>	2 Kb EEPROM; packet buffer size: 2.5 Mb	
<b>Mounting and enclosure</b>	Mounts in an EIA standard 19-inch telco rack (hardware included); wall, desktop and under-table mounting	
<b>Performance</b>	<b>100 Mb Latency</b>	< 5.6 $\mu$ s (LIFO 64-byte packets)



## Technical Specifications

	<b>1000 Mb Latency</b>	< 2.2 $\mu$ s (LIFO 64-byte packets)
	<b>Throughput</b>	up to 6.5 Mpps (64-byte packets)
	<b>Switching capacity</b>	8.8 Gbps
	<b>MAC address table size</b>	8192 entries
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C), noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	15% to 90% @ 149°F (65°C), noncondensing
	<b>Altitude</b>	up to 10,000 ft. (3 km)
	<b>Acoustic</b>	Power: 0 dB No fan
<b>Electrical characteristics</b>	<b>Frequency</b>	50/60 Hz
	<b>Maximum heat dissipation</b>	37 BTU/hr (39.03 kJ/hr)
	<b>AC Voltage</b>	100 - 240 VAC
	<b>Current</b>	0.9 A
	<b>Maximum power rating</b>	10.8 W
	<b>Notes</b>	<p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> <p>The exact input voltage and frequency rating are determined by the specific power adaptor part number ordered. Please select the correct power adaptor country option.</p>
<b>Safety</b>		UL 60950-1; CSA 22.2 60950-1; IEC 60950-1:2005; EN 60950-1:2006 + A11:2009
<b>Emissions</b>		FCC Rules Part 15, Subpart B Class A
<b>Immunity</b>	<b>Generic</b>	EN 55022 CISPR 22
	<b>EN</b>	EN 55024, CISPR 24
	<b>ESD</b>	IEC 61000-4-2
	<b>Radiated</b>	IEC 61000-4-3
	<b>EFT/Burst</b>	IEC 61000-4-4
	<b>Surge</b>	IEC 61000-4-5
	<b>Conducted</b>	IEC 61000-4-6
	<b>Power frequency magnetic field</b>	IEC 61000-4-8
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11
	<b>Harmonics</b>	IEC 61000-3-2
	<b>Flicker</b>	IEC 61000-3-3

## Technical Specifications

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### Standards and protocols **General protocols**

(applies to all products in series)

- IEEE 802.1p Priority
- IEEE 802.3ab 1000BASE-T Gigabit Ethernet over twisted pair (10/100/1000 models only)
- IEEE 802.3i 10BASE-T Ethernet over twisted pair
- IEEE 802.3u 100BASE-TX Fast Ethernet, 100BASE-FX with autonegotiation
- IEEE 802.3x Flow Control

## Accessories

<b>HPE 1410 Switch series accessories</b>	<b>Cables</b>	
	HP LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable	AJ833A
	HP LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable	AJ834A
	HP LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable	AJ835A
	HP LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
	HP LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
	HP LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
	HP LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A
	<b><u>HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable</u></b>	QK732A
	<b><u>HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable</u></b>	QK733A
	<b><u>HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable</u></b>	QK734A
	<b><u>HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable</u></b>	QK735A
	<b><u>HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable</u></b>	QK736A
	<b><u>HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable</u></b>	QK737A
	<b>HP 1410-24G Switch (J9561A)</b>	
	<b><u>HP X111 100M SFP LC FX Transceiver</u></b>	J9054C

## Accessory Product Details

**NOTE:** Details are not available for all accessories. The following specifications were available at the time of publication.

<b>HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)</b>	<b>Cabling</b>	<p><b>Cable type:</b> 50/125 <math>\mu\text{m}</math> (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m</p> <p><b>Maximum distance:</b> 10Gbps Transfer Rate (Ethernet): 300m</p>
	<b>Notes</b>	<p>Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 <math>\mu\text{m}</math> fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.</p> <ul style="list-style-type: none"> <li>• Dimensions: Core diameter: 50 <math>\pm</math> 3.0<math>\mu\text{m}</math> Cladding diameter: 125 <math>\pm</math> 2.0<math>\mu\text{m}</math> Coating diameter: 245 <math>\pm</math> 10<math>\mu\text{m}</math></li> <li>• Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.</li> <li>• Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.</li> <li>• CABLE: The cable is duplex zipcord graded index 50/125<math>\mu\text{m}</math> multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows.</li> <li>• BULK CABLE &amp; CABLE ASSEMBLY CONFIGURATION:</li> <li>• Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.</li> <li>• Jacket Color: Aqua for OM3 multimode per TIA 598</li> <li>• Boot Color: White</li> <li>• Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths &gt; 30 meters.</li> <li>• Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.</li> <li>• Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg</li> </ul>
	<b>Services</b>	<p>Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.</p>

**HP 1 m Multimode OM3 LC/LC Optical Cable (AJ834A)**

**Cabling**

**Cable type:**  
50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

**Maximum distance:**

## Accessory Product Details

### Notes

10Gbps Transfer Rate (Ethernet): 300m

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP 2 m Multimode OM3 Cabling LC/LC Optical Cable

(AJ835A)

#### Cable type:

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

### Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.

## Accessory Product Details

- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP 5 m Multimode OM3 Cabling LC/LC Optical Cable (AJ836A)

#### Cable type:

50/125  $\mu$ m core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

### Notes

Cable Specs: This specification defines the detail requirements for a tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50  $\pm$  3.0um Cladding diameter: 125  $\pm$  2.0um Coating diameter: 245  $\pm$  10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @

## Accessory Product Details

- 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP 15 m Multimode OM3 Cabling LC/LC Optical Cable (AJ837A)

#### Cable type:

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

### Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu\text{m}$  multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP 30 m Multimode OM3 LC/LC Optical Cabling

#### Cable type:

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for

## Accessory Product Details

### Cable (AJ838A)

distances of up to 300 m;

#### Notes

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

#### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP 50 m Multimode OM3 LC/LC Optical Cable (AJ839A)

#### Cabling

#### Cable type:

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

#### Notes

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.



## Accessory Product Details

- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable (QK732A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP Premier Flex LC/LC Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors

## Accessory Product Details

### Multi-mode OM4 2 fiber 2m Cable (QK733A)

on each end.

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

#### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP Premier Flex LC/LC Notes Multi-mode OM4 2 fiber 5m Cable (QK734A)

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

#### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP Premier Flex LC/LC Notes Multi-mode OM4 2 fiber 15m Cable (QK735A)

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

## Accessory Product Details

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable (QK736A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

### Services

Refer to the HP website at <http://www.hp.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable (QK737A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)

## Accessory Product Details

		<ul style="list-style-type: none"> <li>• Jacket Color: Blue</li> <li>• Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic</li> <li>• Boot Color: White</li> <li>• Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.</li> <li>• Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths &gt;30m</li> <li>• Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45</li> </ul>
	<b>Services</b>	<p>Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.</p>
<b>HP X121 1G SFP LC SX Transceiver</b> (J4858C)	<b>Ports</b>	1 LC 1000BASE-SX port; Duplex: full only
	<b>Physical characteristics</b>	<p>Dimensions: 2.24(d) x 0.54(w) x 0.48(h) in. (5.69 x 1.37 x 1.22 cm)          Weight: 0.04 lb. (0.02 kg)          Transceiver form factor: SFP</p>
A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550 m on multimode fiber.	<b>Environment</b>	<p>Operating temperature: 32°F to 158°F (0°C to 70°C)          Operating relative humidity: 5% to 85%, noncondensing          Nonoperating/Storage temperature: -40°F to 203°F (-40°C to 85°C)          Altitude: up to 10,000 ft. (3 km)</p>
	<b>Electrical characteristics</b>	<p>Power consumption typical: 0.4 W          Power consumption maximum: 0.7 W</p>
	<b>Cabling</b>	<p>Type:</p> <ul style="list-style-type: none"> <li>• 62.5/125 μm or 50/125 μm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively;</li> </ul> <p>Maximum distance:</p> <ul style="list-style-type: none"> <li>• 2-220 m (62.5 μm core diameter, 160 MHz*km bandwidth)</li> <li>• 2-275 m (62.5 μm core diameter, 200 MHz*km bandwidth)</li> <li>• 2-500 m (50 μm core diameter, 400 MHz*km bandwidth)</li> <li>• 2-550 m (50 μm core diameter, 500 MHz*km bandwidth)</li> </ul> <p>Cable length: 2-550m          Fiber type: Multi Mode</p>
	<b>Services</b>	<p>Refer to the HP website at <a href="http://www.hp.com/networking/services">http://www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
<b>HP X121 1G SFP LC LX</b>	<b>Ports</b>	1 LC 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX); Duplex: full only
	<b>Physical characteristics</b>	Dimensions: 2.24(d) x 0.54(w) x 0.486(h) in. (5.69 x 1.37 x 1.23 cm)

## Accessory Product Details

### Transceiver (J4859C)

HP X121 1G SFP LC LX  
Transceiver: An SFP  
format  
gigabit transceiver with LC  
connectors using LX  
technology.

#### Environment

Weight: 0.04 lb. (0.02 kg)

Operating temperature: 32°F to 158°F (0°C to 70°C)

Operating relative humidity: 0% to 85%, noncondensing

Nonoperating/Storage temperature: -40°F to 212°F (-40°C to 100°C)

Altitude: up to 10,000 ft. (3 km)

#### Cabling

Type:

- Either single mode or multimode; 62.5/125  $\mu\text{m}$  or 50/125  $\mu\text{m}$  (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1;

Maximum distance:

- 2-550 m (multimode 62.5  $\mu\text{m}$  core diameter, 500 MHz\*km bandwidth)
- 2-550 m (multimode 50  $\mu\text{m}$  core diameter, 400 MHz\*km bandwidth)
- 2-550 m (multimode 50  $\mu\text{m}$  core diameter, 500 MHz\*km bandwidth)
- 2-10,000 m (single-mode fiber)

#### Notes

A mode conditioning patch cord may be needed in some multimode fiber installations.

Wavelength: 1310nm

Power Consumption: < 500mW Typical

#### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

### HP X111 100M SFP LC FX Ports

#### Transceiver (J9054C)

#### Physical characteristics

1 LC 100BASE-FX port (IEEE 802.3u Type 100BASE-FX); Duplex: half or full

#### Dimensions

2.7(d) x 0.54(w) x 0.48(h) in. (6.86 x 1.38 x 1.22 cm)

#### Weight

0.06 lb. (0.03 kg)

#### Environment

**Operating temperature** 32°F to 158°F (0°C to 70°C)

**Operating relative humidity** 5% to 95%

**Nonoperating/Storage temperature** -40°F to 185°F (-40°C to 85°C)

**Nonoperating/Storage relative humidity** 5% to 85%

**Altitude** up to 10,000 ft. (3 km)

#### Cabling

Cable type:

62.5/125  $\mu\text{m}$  or 50/125  $\mu\text{m}$  (core/cladding) diameter, graded-index, low metal

---

## Accessory Product Details

content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively;

Maximum distance:

- 2 km (full duplex) or 412 m (half duplex)

### Notes

Transmitter wavelength: 1310nm

Power consumption is 1.1 watt maximum.

For supported platforms and minimum software requirements to support this product, see the document titled "Support for the J9054C 100-FX SFP-LC Transceiver" on the "ProCurve Mini-GBICs and SFPs" Manuals Web page.

### Services

Refer to the Hewlett Packard Enterprise website at

**<http://www.hpe.com/networking/services>** for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

---

## Summary of Changes

Date	Version History	Action	Description of Change:
01-Dec-2015	From Version 13 to 14	Changed	Overview, Features and Benefits and Technical Specifications updated
01-Dec-2014	From Version 12 to 13	Changed	Updated Warranty and support
16-Dec-2013	From Version 11 to 12	Changed	Updated Introduction.
09-Dec-2013	From Version 10 to 11	Changed	Updates were made throughout the document for the 12/9 refresh.
30-Sep-2013	From Version 9 to 10	Changed	Configuration was revised.
11-Sep-2013	From Version 8 to 9	Added	Configuration was added.
10-Jun-2013	From Version 7 to 8	Added	OM4 cables were added.
28-Oct-2011	From Version 6 to 7	Changed	Changes were made throughout, including changing the title.
30-Sep-2011	From Version 5 to 6	Added	Accessory Product Details was added.
16-Aug-2011	From Version 4 to 5	Changed	Features and benefits and models were revised.
24-May-2011	From Version 3 to 4	Changed	The Accessories section was revised. Two new models were added to the document as well.
09-May-2011	From Version 2 to 3	Changed	The Accessories section was revised. Two new models were added to the document as well.
15-Mar-2011	From Version 1 to 2	Changed	Changes were made throughout, including changing the title.



**Sign up for updates**

★ Rate this document

© Copyright 2015 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hp.com/networking>

c04164469 - 13674 - Worldwide - V14 - 1-December-2015

