



HB **EV12115** TRACTION DRY CELL

Non-Spillable, maintenance-free AGM technology designed for longer cycle life and deep discharge applications. Built to withstand cyclic applications such as Mobile Auxiliary and Emergency Power, Electric tools, Electric Vehicles, Aerial Lifts, Scissor Lifts, Work Platforms, Floor Care Equipment, Materials Handling Equipment, Mobile Renewable Energy, Recreational Vehicle, and Marine.

PRODUCT SPECIFICATIONS:

Harris Battery Part #:	EV12115
Volts:	12
Weight lbs:	67.50
Weight kg:	30.60
Length inches:	13
Length mm:	330.00
Width inches:	6 13/16
Width mm:	173.00
Height inches:	8 11/16
Height mm:	220.00
100 Hour Rate Amp Hours (AH):	119
20 Hour Rate Amp Hours (AH):	115
10 Hour Rate Amp Hours (AH):	110
5 Hour Rate Amp Hours (AH):	97
Reserve Capacity @ 75 Amps:	65
Reserve Capacity @ 25 Amps:	242
Terminal:	T11

NOTES:

- Additional product configurations available with some modules
- Multiple Terminal options available with most models
- Harris Battery provides responsible battery recycling
- Warranty references product application
- Image may differ from actual product available