

**FOAMLOGIX® 2.1A PRICE LIST AND ORDER FORM****FAX ORDER DIRECTLY TO CLASS 1: 352-629-2902**

Sales Order Number: \_\_\_\_\_ Date: \_\_\_\_\_  
Ordered By: \_\_\_\_\_ Customer: \_\_\_\_\_  
Hale Customer#: \_\_\_\_\_ Customer PO# \_\_\_\_\_  
Customer Job/Truck #: \_\_\_\_\_ Due Date: \_\_\_\_\_  
Fire Dept.: \_\_\_\_\_ Fire Dept. Contact: \_\_\_\_\_  
Fire Dept. Phone: \_\_\_\_\_ Fire Dept. Fax: \_\_\_\_\_

**Package A****Part Number: (Choose One)**

- FLX21-12-1-10-1 (12 Volt)  
 FLX21-24-1-10-1 (24 Volt)

**Description: FoamLogix 2.1A Kit (12 Volt) with *single* stainless steel check valve manifold**

Includes the following:

- (1) FoamLogix full function digital display control that displays flow, foam %, total flow and total foam
- (1) 2.1 GPM foam pump assembly with strainer bypass and service valves.
- (1) 15 feet of cable between display and pump and 10 feet of cable between display and flow sensor
- (1) Compact foam manifold assembly with a single waterway check valve, flow sensor and foam injection check valve installed. 3 inch grooved victaulic connections.  
Flow range 30 - 750 GPM  
Note: A second check valve is recommended to avoid pump/water tank contamination.
- (1) Installation kit includes clear reinforced foam inlet hose, hose clamps, positive and ground terminal insulation kit.
- (2) Operation and Installation manuals.
- (1) Single tank system instruction placard
- (1) Side mount low level tank sensor

**List Price \$3,824****Package B****Part Number: (Choose One)**

- FLX21-12-2-10-1 (12 Volt)  
 FLX21-24-2-10-1 (24 Volt)

**Description: FoamLogix 2.1A Kit (12 Volt) with *dual* stainless steel valve manifold (recommended for NFPA backflow prevention compliance):**

Includes the following:


- (1) FoamLogix full function digital display control that displays flow, foam %, total flow and total foam
- (1) 2.1 GPM foam pump assembly with strainer bypass and service valves.
- (1) 15 feet of cable between display and pump and 10 feet of cable between display and flow sensor
- (1) Foam manifold assembly with dual waterway check valves, flow sensor and foam injection check valve installed. 3 inch grooved Victaulic connections.  
Flow range 30 - 750 GPM
- (1) Installation kit includes clear reinforced foam inlet hose, hose clamps, positive and ground terminal insulation kit.
- (2) Operation and Installation manuals.
- (1) Single tank system instruction placard
- (1) Side mount low level tank sensor

**List Price: \$4,102**


## LOW TANK SENSORS OPTIONS

One sensor required for foam concentrate tank. (Please check option desired.)


TANK SENSOR OPTIONS (PLEASE CHOOSE ONE)		
	DESCRIPTION	TANK A
	TOP MOUNT SENSOR	\$358
	SIDE MOUNT SENSOR	\$89
	BOTTOM MOUNT SENSOR	\$126



**Top Mount Sensor**



**Side Mount Sensor**



**Bottom Mount Sensor**

## Options

- 20' cable between display and pump and 15' of cable between display and flow sensor.
- P/N 112074 2-inch Single Check Manifold \$266
- Remote Start/Stop option \$346