

Service Bulletin



June 22, 2021

SERVICE BULLETIN: SB 21-03

PRODUCT NAME: INFORMATION CENTER

PART NUMBER:

111267



610-00057

6205-0002-00



INFORMATION CENTER

The Information Center provides status and diagnostic control functions for a vehicle equipped with a Class 1 ES-Key Multiplex System or Weldon V-MUX System. The Information Center has a display (4 lines, 20 characters each) and six (6) buttons. Three (3) buttons have dedicated usage (escape, scroll up, scroll down). The three (3) buttons below the display are “soft buttons,” whose function is dictated by the displayed text above the associated button.

PRODUCT UPDATES

- 111267 INFO CENTER and 6205-0002-00 VFD are consolidating to part number 610-00057
- Once it boots up, you can choose ES-Key, V-MUX, or Terminal
 - There is a method to go back to set-up screen again (hold escape key while power is applied or enter a password)
 - Once a mode is selected, it operates the same as the previous version
- ARM PROCESSOR – Increased processing power to accommodate larger FLEX files
- Expanded capacity memory – 1024 to 1984 number of I/Os
- Still backward compatible with USM

LIST PRICE (US Dollars, FCA Free Carrier Our Dock, Wooster, OH USA Incoterms® 2010)

Style #	Description	\$Price
610-00057	INFORMATION CENTER	\$910

AVAILABILITY

June 2021

SPECIFICATION

- Voltage range +9VDC...+32VDC
- Power consumption@13.8VDC Logic supply+ input (pin 1) 180mA
- Operational temperature range -40°C...+85°C
- Environmental range IP 10
- CAN specification SAE J1939 proprietary, 250 Kbits/second
- Protection
- Internal thermal fuse (2.5A on pin 1)
- Reverse voltage protection (pins 1 and 2)
- CAN buses protected to 24V
- ESD voltage protected to SAE J1113 specification for heavy-duty trucks (12V)
- Transient voltage protected to SAE J1113 specification for heavy-duty trucks (12V)
- Load dump voltage protected to SAE J1113 specification for heavy-duty trucks (12V)
- (backlighting is not protected from load dump)
- Dimensions (W x L x H) in inches [mm] 6.000 [152.40] x 4.437 [112.70] x 1.530 [38.86]