

Class 1

UltraView

UV-750



FEATURES

- J1939 CAN Based Display (3 ports)
- Fully ES-Key compatible
- Easily retrofitted on existing Es-Key systems
- Bonded LCD screen viewable in direct sunlight
- Fully configurable by the OEM
- Multiple languages
- Flexible mounting options: Flush mount, rear mount or gimbal mount
- Sealed to IP-67 front and rear
- Operating temperature range -40° to +85° C

SPECIFICATIONS

- Display: 7"/178mm color transmissive TFT LCD
- Resolution: WQVGA 800 x 480 pixels, 16 bit color
- Landscape or portrait orientation
- NTSC/PAL video input
- Industry standard Deutsch connectors
- 3 configurable analog inputs
- 1 digital output 500mA
- 8-35 VDC operating voltage



Class 1

UltraView

UV-450



FEATURES

- J1939 CAN Based Display (2 ports)
- Fully ES-Key compatible
- Easily retrofitted on existing Es-Key systems
- Bonded LCD screen viewable in direct sunlight
- Fully configurable by the OEM
- Multiple Languages
- Flexible mounting options: Flush mount, rear mount or gimbal mount
- Sealed to IP-67 front and rear
- Operating temperature range -40° to +85° C

SPECIFICATIONS

- Display: 4.3" color transmissive TFT LCD
- Resolution: WQVGA 480 x 272 pixels, 16 bit color
- Landscape or portrait orientation
- NTSC/PAL video input
- Industry standard Deutsch connectors
- 2 configurable analog inputs
- 1 digital output 500mA
- 8-35 VDC operating voltage