



OVERVIEW

The REL-2 is a prime component when it comes to controlling anything from your floor heater & slide room switches to your generator or pump switches. Equipped with 2 independent dry contact relay outputs and 2 auxiliary inputs, the REL-2 will suite your basic needs in switch control. LED indicators are provided at each output for quick status identification. The 2 auxiliary inputs can be used to send status signals back to their switches or be configured as simple switches using the V-Bus Studio software. Fail-Safe timers can be configured to turn-off outputs in the event the controlling switch becomes disconnected. The REL-2 is armed with reverse battery protection and sealed in a potted box enclosure for the best durability. With an easy 2-hole mounting system and a 9-position Mate-N-Lock connector, installing the REL-2 to your V-Bus network will be a simple task.

FEATURES

- Easy Installation
- (2) Relay Outputs
- (2) Auxiliary Inputs
- Digitally Configured Output Settings
- Reverse Battery Protection
- Fail-Safe Timers
- Output Cycle Timers
- LED Output Status Indicators
- Sealed Potted Box Enclosure
- Easy 2-hole mounting
- 9-Position Mate-N-Lock Connector
- Uses V-Bus Technology

OUTPUT SETTINGS

- Straight On/Off
- Input mapping
- Input switch polarity
- Fail-safe time
- Output cycle time

SPECIFICATIONS

- 12v Operation
- -20°C to 85°C Operation
- Standby Current < 1mA
- 5A Max each Output
- O.A. Dimensions (2.1"W x 4.0"H)



**EXPANDING THE
POSSIBILITIES**

2504 JEANWOOD DRIVE
ELKHART, IN 46514
p: (574) 262-0518
f: (574) 262-5172