




3" Surface Mount Series

FEATURES

- 9 Diodes •
- Surface Mount •
- With or Without a Switch •
- 2 Bare Wires •
- 3 Screw Holes •
- 12 Volt •



L09-0114-SW



2 Bare Wire



L09-0114-NW-SW

PART #'S & INDIVIDUAL SPECS



L09-0113

<p><u>L09-0113</u></p> <p>Current: 201.57 mA Power: 2.58 W Illum: 11.7 lx @ 7' CCT: 5500K ± 200 CRI: 85</p>	<p><u>L09-0114-SW</u></p> <p>Current: 199.5 mA Power: 2.55 W Illum: 11.2 lx @ 7' CCT: 3500K ± 200 CRI: 85</p>
<p><u>L09-0113-NW</u></p> <p>Current: 195.3 mA Power: 2.5 W Illum: 11.3 lx @ 7' CCT: 3500K ± 200 CRI: 85</p>	<p><u>L09-0114-NW-SW</u></p> <p>Current: 200.1 mA Power: 2.56 W Illum: 11.2 lx @ 7' CCT: 3500K ± 200 CRI: 85</p>



L09-0113-NW

BENEFITS

- Inexpensive & Economical •
- 2 Color Temperatures •
- Small Design Fits in Extra Tight Spaces •
- Exceptional Brightness from Compact Design •



Kaper II, Inc.
1-800-336-2011
www.kaperii.com