


Tank Monitor V2 Control

Description

Electronic control module that controls four output relays for water pumps, fuel pumps, and lighting. Also provides capability to monitor fuel/LP tank levels as well as fresh/black/grey water tank levels. Control is compatible with LCI myRV® line of CAN networked products, allowing for remote operation of LCI product via LCI OneControl™ tablet and mobile apps.




Applies to

Part #	Description
21422-A	LCI Tank Monitor V2 Control (20 A)
21569-A	LCI Tank Monitor V2 Control (10 A)

Key Features

- Six fresh/black/grey water monitor inputs
- Three fuel/LP tank monitor inputs
- One gas heater ignition feedback
- Chassis battery monitor
- Two 10-amp output controls
- Two 20-amp output controls
- Fully compatible with LCI myRV® line of CAN enabled products - plug-and-play operation with existing myRV® systems
- Remote control via OneControl™ tablet and mobile apps when connected to myRV® systems



Electrical Characteristics

Rating	Symbol	Min	Typ	Max	Unit
Operating Supply Voltage	V_{batt}	9	13.8	16	Volts DC
Output Current	I_{out}			30	A
Resting Current	I_{rest}			100	mA



Additional Notes

- Power input feed must be protected by a 30A Fuse or Mini Breaker MAX line
- Heater feedback – if after 30 seconds the heater feedback is not on, then the gas heater relay will turn off