



- NOTES:**
- 1) ALL HOOK UP WIRE SHALL BE RATED AT 600V MINIMUM, UL LISTED, #18AWG, BLUE, UNLESS OTHERWISE NOTED.
 - 2) BRANCH CIRCUIT PROTECTION PROVIDED BY CUSTOMER. CONNECT TO GFCI AND ACCORDING TO LOCAL ELECTRICAL CODE.
 - 3) RESET LIGHT OFF WHEN RESET SWITCH IS SELECTED
 - 4) OVERRIDE LIGHT OFF WHEN OVERRIDE SWITCH IS SELECTED
 - 5) AIR LIGHT OFF WHEN AIR IS NOT PRESENT
 - 6) PAUSE LIGHT OFF WHEN PAUSE SWITCH IS PUSHED

		TITLE: SCHEMATIC, COMPUTER CONTROL ASSY, BRIDGE MACHINES	
		DRAWING BY: WILL BREWER DATE: 10/29/10	MATERIAL / SPECIFICATION SEE BOM
PROPRIETARY INFORMATION THIS DRAWING IS THE PROPERTY OF OMAX CORPORATION AND NOT TO BE COPIED OR REPRODUCED WITHOUT THE WRITTEN CONSENT OF OMAX CORPORATION.		REVISED BY: WILL BREWER DATE: 08/03/12	SCALE: . SHEET 1 OF 1 SIZE C
		DWG NO. 400673E	