
Pinout for Power Technology Remote Leads

| Pin# | Colors | Use |
|------|-------------------------------|------------------------------------|
| Α | White & Black | Analog Temp Sender |
| В | Black & Orange (Twisted Pair) | Can High |
| С | White & Orange (Twisted Pair) | Can Low |
| D | Red & White | 12vdc+ for Gauges |
| E | Green | Ground |
| F | Gray | Ignition 12vdc+ |
| G | Red | Battery 12vdc+ |
| Н | White & Red | Start /Stop Circuit |
| J | Orange | LED (For units with 3,4,7 in Sixth |
| | | Character of S/N) |
| K | Brown & White | Analog Oil pressure sender |

All Remote Leads Head End Uses (Plug P/N: 06P3822) (Pin P/N: 06P31076) (Wire Seal P/N: 06P39008) (Cavity Plug P/N: 06P39011) Remote leads

07LRU Lead Contains Wires as Follow

| Pin # | Colors |
|-------|----------------|
| Α | White & Black |
| В | Black & Orange |
| С | White & Orange |
| D | Red & White |
| E | Green |
| F | Gray |
| G | Red |
| Н | White & Red |
| J | Orange |
| K | Brown& White |



07LRTG Lead Contains Wires As Follow (Tail End Uses Plug P/n:

| | | Tail End Plug P/N | Position |
|---|-------|-------------------|----------|
| В | Black | 06PH2140-10 | J6-4 |
| С | White | 06PH2140-10 | J6-5 |
| E | Green | 06PH2140 | J4-3 |
| G | Red | 06PH2140 | J4-1 |

07LRU Leads Contain wires as follows

| Pin # | Wire Color |
|-------|------------------------------|
| Α | White & Black (Twisted Pair) |

Pinout for Power Technology Remote Leads

| В | Black & Orange (Twisted Pair) |
|---|-------------------------------|
| С | White & Orange |
| D | Red & White |
| E | Green |
| F | Gray |
| G | Red |
| Н | White & Red |
| J | Orange |
| K | Brown & White |