

MOBILE DEVICE CHARGING CENTERS

USB
INPUT: 12-28 VDC

RVs - BUSES - BOATS - TRAILERS - TRUCKS



Part Dimensions:
h: 2.75 (69.85 mm)
w: 2.25 (57.15 mm)
d: 1.50 (38.10 mm)

SP0192-15-A0311

Charges: 2 phones or 1 phone + 1 tablet

- Output: 5V 2.4 Amp Dual USB
- Input: 12-28 VDC
- FCC Compliant
- Device Protection: Voltage Overload, Secondary Internal Fuse & Capacitor
- Reverse Polarity Protection
- Ignition Protection
- Flame Resistant Nylon UL 94V-0
- 1.5 Depth / 6-inch 20-Gauge Wire
- Available: Black, Ivory and White

SP0192-15-A0312

Rapid Charges: 2 phones or 2 tablets

- Output: 5V 4.8 Amp Dual USB
- Input: 12-24 VDC
- FCC Compliant
- Device Protection: Voltage Overload, Secondary Internal Fuse & Capacitor
- Reverse Polarity Protection
- Ignition Protection
- Flame Resistant Nylon UL 94V-0
- 1.5 Depth / 6-inch 20-Gauge Wire
- Available: Black, Ivory and White