

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 2015

© COPYRIGHT 2010 BY TE CONNECTIVITY

ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS				
P	LTR	DESCRIPTION	DATE	DWN	APVD	
		NC	NEW RELEASE PER E.O. P20485	06AUG2010	IG	RDR
		A	REVISED PER E.O. P20776	04FEB2011	IG	RDR
		B	REVISED PER ECO-15-005416	22JUL2015	JA	DM

MAIN POLARIZING KEY
4X SIZE 16
3X SIZE 4

1.521±.025 [38.63±0.63]
Ø1.950 [49.53] OVER KNURL
Ø1.470 [37.34]

COUPLING RING
PLUG HOUSING
RETAINING RING

GROMMET
POLARIZING INDICATOR
DATE CODE
HDP26-24-7SN-C038

POLARIZING INDICATOR
DATE CODE

5. 3 SIZE 4: 4 AWG [21.0-25.0 mm²] AND 4 SIZE 16.

4 NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.

3 MATERIAL: PLUG HOUSING/COUPLING RING: PA66 GF10 (BLACK)
RETAINING RING: PA66 GF10 (GREEN)
GROMMET: SILICONE (ORANGE-RED)

2 SEE 0425-021-0000 APPLICATION SPECIFICATION
A. RECOMMENDED WIRE INSULATION RANGE
B. CONTACT REMOVAL TOOL

1. THIS PLUG MATES WITH HDP24-24-7PX-XXXX RECEPTACLE
X = SEAL TYPE (N,T,E)
XXXX = MODIFICATION

NOTES:

TE INTERNAL PN	DEUTSCH PN
HDP26-24-7SN-C038	HDP26-24-7SN-C038

DIMENSIONS: INCHES [mm]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN 01APR2010 ILINA GRANICHAROVA		TE Connectivity	
		0 PLC	±	CHK 05AUG2010 BRICE BYFORD	TE		NAME PLUG CONNECTOR SHELL SIZE 24, -C038 MOD HDP SERIES
		1 PLC	±	APVD 05AUG2010 STEVE BEARD			
		2 PLC	±	PRODUCT SPEC	SIZE A3 CAGE CODE 4AFU8 DRAWING NO. HDP26-24-7SN-C038		RESTRICTED TO -
		3 PLC	±.015 [0.38]	APPLICATION SPEC 0425-021-0000			
		4 PLC	±	WEIGHT 52.08g	SCALE 2:1 SHEET 1 OF 1 REV B		
		ANGLES	±0°30'0"	Customer Drawing			
MATERIAL 3		FINISH					

1470-19 (3/11)