



Pantheon
MA750.A.ABICG.003

Specification

Part No.	MA750.A.ABICG.003
Product Name	Pantheon Antenna 5in1 MA.750 Screw-Mount (Permanent Mount) <ul style="list-style-type: none"> • 2G/3G/4G (MIMO) • GPS-GLONASS • 2.4/5GHz (MIMO)
Feature	<ul style="list-style-type: none"> • 2 x Cellular (2G/3G/4G) Antennas (MIMO) (698~960MHz, 1710~2170MHz,2300~2700MHz, 2900~3500MHz) <ul style="list-style-type: none"> • 1*MIMO main antenna • 1*MIMO diversity antenna • 1 x GPS/GLONASS 1575.42/1602MHz Active Antenna • 2 x 2.4GHZ/ 5GHz Antennas (MIMO) <ul style="list-style-type: none"> • 1*MIMO main antenna • 1*MIMO diversity antenna IP67 Waterproof Front End SAW Filter High Efficiency / Peak Gain Outdoor Antenna RoHS Compliant



1. Introduction

The MA.750 Pantheon antenna is an omni-directional heavy-duty, fully IP67 waterproof external M2M antenna for use in telematics, transportation and remote monitoring applications.

This unique antenna delivers powerful MIMO antenna technology for cellular/LTE and Wi-Fi 802.11n and emerging 802.11ac, plus GPS/GLONASS for next generation multiple wireless technology systems, such as telematics. The GPS/GLONASS antenna has a Front End SAW Filter.

Examples are new fleet management and real time video applications that demand high speed video uplink and downlink. High efficiency and high gain MIMO antennas are necessary to achieve the required signal to noise ratio and throughput required to solve these challenges.

Five (5) high performance antennas are integrated into an extremely robust IP67 direct/permanent mount antenna package with excellent isolation (20dB+).

The antenna has its own ground-plane and can radiate on any mounting environment like metal or plastic without affecting performance. The cables are low loss allowing for lengths of up to 10 meters (32' and 9.70"), critical for buses, trains and other commercial transport applications.

Customized cables and connector version available.

2. Specification

2G/3G/4G MIMO					
Frequency	698~960	1710~2170	2300~2700	2900-3500	MHz
VSWR	3 Max				
Polarization	Vertical				
Impedance	50				Ω

2.4GHz/ 5GHz MIMO			
Frequency	2.4~2.5	4.5~5.85	GHz
VSWR	2 Max		
Polarization	Linear		
Impedance	50		Ohm

GPS-GLONASS						
Centre Frequency	1575.42MHz / 1602MHz					
Bandwidth	10MHz					
Radiation Efficiency	50(without cable)					
Passive Gain @ Zenith	4.0 typ(with $\psi=140$ mm ground)					
VSWR	2					
Impedance	50Ω					
DC Power Input Range	3 ~ 5V					
DC input	3.3V		4.0V		5.5V	
MHz	1575.42	1602	1575.42	1602	1575.42	1602
VSWR	2	2	2	2	2	2
LNA Gain	29.2	29	31	31	32.3	32
Noise Figure	3.1	3.1	3.2	3.2	3.4	3.4
Power Consumption	7.5	7.5	9.4	9.4	15	15
Band Attenuation	1520MHz: -20dB 1642MHz: -20dB		1520MHz: -20dB 1642MHz: -20dB		1520MHz: -20dB 1642MHz: -20dB	
Cable	3m RG-174 standard, fully customizable					
Connector	SMA(M) standard, fully customizable					

2. Specification


MECHANICAL	
Antenna Dimensions	Height 85.7mm x Diameter 145.6mm
Casing	Wonderloy PC-540 PC/ABS Alloy
Waterproof	IP67
2G/3G/4G MIMO 1	3M CFD-200 SMA(M)
2G/3G/4G MIMO 2	3M CFD-200 SMA(M)
2.4/5GHz MIMO 1	3M CFD-200 RP-SMA(M)
2.4/5GHz MIMO 2	3M CFD-200 RP-SMA(M)
GPS/GLONASS	3M RG-174 SMA(M)
Base and thread	CAN10 Zinc Alloy
Thread diameter	M30 x 2 (30mm)
Nut	Nickel Plated Steel
Foam	3M 9448HK
Water	IP67
Weight(kg)	1.29 (Antenna) / 1.53 (With box)
Recommended Torque for Mounting	49 N·m
Max Torque for Mounting	58.8N·m
ENVIRONMENTAL	
Operation Temperature	-40°C to 85°C
Storage Temperature	-40°C to 90°C
Humidity	Non-condensing 65°C 95% RH

* All measurements were conducted with 3m low loss CFD200 cable


3. LTE MIMO

3.1 LTE MIMO 1 and LTE MIMO 2 Specification

3.1.1 Return Loss




3.1.2 Maximum Gain




3. LTE MIMO

3.1 LTE MIMO 1 and LTE MIMO 2 Specification

3.1.3 Average Gain



3.1.4 Efficiency





3.2 Radiation Patterns





3.2.1 LTE MIMO 1 Radiation Pattern

XY Plane





3.2.1 LTE MIMO 1 Radiation Pattern

XY Plane





3.2.1 LTE MIMO 1 Radiation Pattern

XZ Plane





3.2.1 LTE MIMO 1 Radiation Pattern

XZ Plane





3.2.2 LTE MIMO 2 Radiation Pattern

XY Plane





3.2.2 LTE MIMO 2 Radiation Pattern

XY Plane





3.2.2 LTE MIMO 2 Radiation Pattern

XZ Plane



3.2.2 LTE MIMO 2 Radiation Pattern


XZ Plane




4. 2.4 / 5GHz MIMO

4.1 2.4/5 GHz MIMO 1 and MIMO 2 Specification

4.1.1 Return Loss




4.1.2 Maximum Gain




4. 2.4 / 5GHz MIMO

4.1 2.4/5 GHz MIMO 1 and MIMO 2 Specification

4.1.3 Average Gain



4.1.4 Efficiency





4.2 Radiation Patterns




4.2.1 2.4/5GHz MIMO 1

XY Plane




4.2.1 2.4/5GHz MIMO 1

XY Plane




XZ Plane




4.2.1 2.4/5GHz MIMO 1

XZ Plane





XZ Plane




4.2.2 2.4/5GHz MIMO 2

XY Plane




4.2.2 2.4/5GHz MIMO 2

XY Plane





XZ Plane




4.2.2 2.4/5GHz MIMO 2

XZ Plane




5. GPS/GLONASS

5.1 Block Diagram



5.2 Return Loss




5.3 GPS/GLONASS Antenna Radiation Pattern




XYZ Co-Ordinates for Reference


XZ-plane
Free Space
@1575.42MHz




YZ-plane
Free Space
@1575.42MHz





XZ-plane
Free Space
@1602MHz





YZ-plane
Free Space
@1602MHz



5.4 GPS/GLONASS LNA




6. Drawing




Name	Material	Finish	QTY
1 Housing	PC 540	Black	1
2 Closed Cell Foam	CR 4305	Black	1
3 M30 Nut	Steel AISI 1215	Ni Plated	1
4 Washer	Steel AISI 1215	Ni Plated	1
5 Waterproof Gasket	Silicon Rubber	Black	1
6 Heat Shrink Tube	PE (RG174)	Black	1
7 Heat Shrink Tube	PE (CFD200)	Black	4
8 Rubber Stopper	Silicon Rubber	Black	1
9 GPS-Glonass Label	Coated Paper	Orange	1
10 2.4/5 GHz MIMO1 Label	Coated Paper	Green	1
11 2.4/5 GHz MIMO2 Label	Coated Paper	Lightgreen	1
12 2G/3G/4G MIMO1 Label	Coated Paper	Gray	1
13 2G/3G/4G MIMO2 Label	Coated Paper	White	1

Name	Material	Finish	QTY
UU Cable Length	3000mm \pm 30mm		
VV Cable Type	RG174	Black	1
WW Cable Type	CFD200	Black	4
XX Connector Type	SMA(M) ST	Gold	1
YY Connector Type	RP-SMA(M) ST	Gold	2
ZZ Connector Type	SMA(M) ST	Gold	2

7. Installation



Recommended Torque for Mounting 49 N·m
 Maximum Torque for Mounting 58.8 N·m




**Thread
 Diameter**

**Recommended
 Mounting Hole**

Unit: mm

8. Packaging

1 Antenna per Individual Box
Weight: 1.53Kg




Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without

notice. Taoglas reserves all rights to this document and the information contained herein.


Reproduction, use or disclosure to third parties without express permission is strictly prohibited.

Copyright © Taoglas Ltd.

8 individual boxes per carton



32 cartons per pallet (110*110cm)
256 pieces per pallet



Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without

notice. Taoglas reserves all rights to this document and the information contained herein.

Reproduction, use or disclosure to third parties without express permission is strictly prohibited.

Copyright © Taoglas Ltd.