Revised 11/24/09 Replaces 11/24/09 Printed 11/24/09

SECTION 1 - COMPANY IDENTIFICATION

Catalog / Sub-assembly Number: 746978

National Graphic Supply Inc.

1848 West 11th Street

Suite H

Jpland, CA. 91786

TRANSPORTATION EMERGENCIES (24HR)

Inside US/Canada 800-424-9300

General Info 800-779-5657 24 Hour Contact 909-261-9225

FAX 909-981-6332

FOR INDUSTRIAL USE ONLY.....USE ONLY AS DIRECTED.....DO NOT TAKE INTERNALLY!

| SECTION 2 - COM | MPOSITION / INFOR | MATION ON | INGREDIENTS | |
|---------------------|-------------------|-----------|---------------------|------------------|
| Ingredients | CAS Number | Wt.% | OSHA PEL (mg/m3) | ACGIH (mg/m3) |
| Diethylene Glycol | 111-46-6 | 3-7% | NE | NE |
| Hydroquinone | 123-31-9 | 3-7% | 2 | 2 |
| Potassium Carbonate | 584-08-7 | 7-15% | NE | NE |
| Potassium Hydroxide | 1310-58-3 | 1-5% | 2 C | 2 C |
| Potassium Sulfite | 10117-38-1 | 3-7% | NE | NE |
| Sodium Sulfite | 7757-83-7 | 1-5% | NE | NE |
| Water | 7732-18-5 | 60-80% | NE | NE |

NE=Not Established STEL=Short Term Exposure Limit C=Ceiling Limits

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Appearance: Clear, pale yellow, aqueous liquid

Odor: slight alkali odor

Wear equipment to protect eyes, skin and respiratory tract. Dike or absorb spills to keep material and run-off from entering sewer or waterways. Use water to cool containers and disperse vapors.

3ox may contain multiple containers having multiple components. Consult all MSDSs.

HMIS: Health: 2 Flammability: 1 Reactivity: 0 Protection: C NFPA: Health: 2 Flammability: 1 Reactivity: 0 Spec. Haz.: None

Hazard Rating: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

A = Gloves B = Gloves & Goggles C = Gloves, Goggles & Apron

D = Face Shield, Gloves, Goggles & Apron

JN NO: None

DOT GUIDE: ERG Guide 111

310540 - NAT-540 FINE LINE LIQUID DEVELOPER-I, 4 x 1 Gallon Fuji Hunt Photographic Chemicals, Inc.

Revised 11/24/09 Replaces 11/24/09 Printed 11/24/09

SECTION 3 - HAZARDS IDENTIFICATION (Cont.)

Potential Health Effects:

Skin: Contact causes irritation.

Eyes: Causes irritation. Direct contact or vapor concentrations

greater than Threshold Limiting Value (TLV) of Hydroquinone may

cause permanent eye damage.

Inhalation: Irritant to respiratory tract and mucous membranes. Ingestion: Ingestion of product may cause nausea and vomiting.

Conditions aggravated by exposure:

Allergic reaction to sulfites may cause respiratory distress.

N

SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush with COOL water for 15 minutes. Call a

physician.

Skin Contact: In case of skin contact; immediately flush with cool water for

15 minutes. Call a physician.

Ingestion: In case of ingestion; seek immediate medical attention.

Inhalation: Immediately remove victim to fresh air. Call a physician for

further recommendations.

SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties

Flash Point: None deg F (TCC) Autoignition Temperature: N/A deg F (CC)

Explosion Limits: Lower: N/A vol.%: Not Tested

Upper: N/A vol.%:

Extinguishing Media:

Choose extinguishing media suitable for the surrounding materials, such as water spray, dry chemical, alcohol foam or carbon dioxide.

Jnsuitable Extinguishing Media:

No restrictions on media based on knowledge of this material.

Fire Fighting Instructions:

Water spray should be used to cool fire exposed containers and to disperse un-ignited vapors. Use NIOSH/MSHA approved positive pressure self-contained breathing apparatus when material has ignited or becomes involved in a fire. Try to remove material containers from fire area if can be accomplished without risk to personnel.

Evacuate area and fight fire from a safe distance. Call your local fire department. Wear positive pressure, breathing apparatus and protect eyes and skin. Use water to cool fire-exposed containers, to protect personnel and to disperse vapors and spills. Fire media run-off can damage the environment. Dike and collect media used to fight fire.

310540 - NAT-540 FINE LINE LIQUID DEVELOPER-I, 4 x 1 Gallon Fuji Hunt Photographic Chemicals, Inc.

Revised 11/24/09 Replaces 11/24/09 Printed 11/24/09

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Small Spills:

For incidential spills and leaks, wear adequate personal protective equipment, see Section 8 (Exposure & Personal Protection). Spills should be contained by, and covered with suitable absorbent material and removed for disposal. Dispose of according to local and national regulations. from entering into soil, waterways and groundwater.

For larger spills, requiring emergency response, neoprene boots and respiratory protection may also be required. Follow OSHA regulations and NIOSH recommendations for respiratory protection (see 29 CFR 1910.134 and NIOSH pub. 87-108) and emergency response (see 29 CFR 1910.120). Hold in properly labeled DOT-approved waste container. Dike large spills to minimize the spill area. Material can cause environmental damage.

SECTION 7 - HANDLING / STORAGE

Handling:

Avoid contact with eyes, skin or clothing. Avoid breathing mist or vapor. Do not swallow. Wear chemical safety goggles and neoprene gloves and apron. Wash thoroughly after handling. Keep container closed when not in use. only with adequate ventilation. Direct contact or vapor concentrations greater than Threshold Limiting Value (TLV) may casue permanent eye damage. ************************

** The National Toxicology Program (NTP) has found that Hydroquinone shows some e vidence of carcinogenic potential in animals; however, the International Agenc y for Research on Cancer (IARC) has determined inconclusive evidence exists on Hydroquinone's carcinogenic potenital in animals.

** Note: NTP, OSHA and IARC do not place Hydroquinone on their lists of suspecte d carcinogens.

Storage:

Store in a cool, dry, well-ventilated area. Keep container closed when not in use.

SECTION 8 - EXPOSURE CONTROL AND PERSONAL PROTECTION

Ventilation:

Good general ventilation should be sufficient for most processing operations. Vent work area to ensure airborne concentrations are below the current occupational exposure limits. Ten (10) or more room air changes per hour containing a minimum of 15% fresh air will meet these requirements. Consult ASHRAE 62-1989 for further requirements.

Personal Protective Equipment

Respiratory Protection: If used under normal operating conditions and with adequate ventilation, respiratory protection is not required. However, refer to OSHA 29 CFR 1910.13 4.

Neoprene gloves and apron Skin Protection: Eye Protection: Chemical safety goggles

810540 - NAT-540 FINE LINE LIQUID DEVELOPER-I, 4 x 1 Gallon Replaces 11/24/09 Fuji Hunt Photographic Chemicals, Inc.

Revised 11/24/09 Printed 11/24/09

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, pale yellow, aqueous liquid

slight alkali odor Odor:

Change in Physical State:

Boiling Point: >100 deg C

Melting Point: N/D deg F
Specific Gravity: 1.27
Vapour Pressure: ~15 Water=1 mmHq @ 20C

Viscosity: N/ASolubility in Water: Complete 10.77 pH Value:

VOC (lbs/gal): 0 (USEPA Method 24)

SECTION 10 - STABILITY AND REACTIVITY

Hazardous Polymerization:

Hazardous polymerization WILL NOT occur if product is used and stored as directed. Product is stable if used and stored as directed.

Hazardous Decomposition Products:

Oxides of Sulfur; Oxides of Carbon; Oxides of Nitrogen; Ammonia Materials and Conditions to Avoid:

Keep away from excess heat. Avoid contact with strong oxidizers, strong acids and strong bases.

SECTION 11 - TOXICOLOGICAL INFORMATION

?roduct Information

LD50 (oral, rat): >2,000 mg/kg

Acute Overexposure:

Skin, eye, mucous membrane and respiratory tract irritant.

Chronic Overexposure:

Prolonged or repeated exposure can cause allergic skin reaction, anemia and weakness.

Ingredient information:

No other information.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity Data: No Data Available Chemical Fate Data: No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Hazardous Waste Characteristic:

None

Recommendation:

Dispose of contaminated product, empty containers and materials used in cleaning up spills or leaks in a manner approved for this material. Consult appropriate federal, state and local regulatory agencies to ascertain proper disposal procedures. Discharge of processing effluent to the sewer may require a permit. DO NOT discharge effluent solutions to septic systems.

Revised 11/24/09 Replaces 11/24/09 Printed 11/24/09

SECTION 14 - TRANSPORTATION INFORMATION

Fround Shipping Information

Proper Shipping Name: Chemicals, N.O.I., Not D.O.T. regulated.

Hazard Class: None UN/NA Number: None Packing Group: None

Air (ICAO/IATA) Shipping Information

Proper Shipping Name: Chemicals, N.O.I., Not D.O.T. regulated.

Hazard Class: None
UN No: None
Packing Group: None
Subsidiary Risk: None
UN/DOT Labels Needed: None

International Maritime Organization (IMO) Additional Shipping Class:

IMDG Code: Not Applicable

Amdt. Code: Amdt. N/A

HTS Code: Not Applicable

Product is labeled in accordance with US D.O.T. 49 CFR.

Further information:

Please call 1-800-779-5657 for further D.O.T. information.

SECTION 15 - REGULATORY INFORMATION

**Note: The ingredient information listed in this section is provided for reporting requirements as dictated by USEPA, state and local regulation. If ingredient is listed in this section but not in Section 2, then the concentration of this ingredient is below de minumis (less than 0.1%).

J.S. FEDERAL REGULATIONS:

313 = SARA Title III Section 313 (40 CFR 372 -- Toxic Release Inventory)

355 = SARA Title III Section 302 (40 CFR 355 -- Extremely Hazardous Substance)

302 = SARA Title III Section 304 (40 CFR 302 -- Hazardous Substance List)

CWA = Clean Water Act Priority Pollutants List

CAA = Clean Air Act 1990 Hazardous Air Contaminants

HAP = Clean Air Act - HON Rule - HAPs

| Ingredients | CAS Number | 313 | 355 | 302 | CWA | CAA | HAP |
|---------------------|------------|-----|-----|-----|-----|-----|-----|
| Diethylene Glycol | 111-46-6 | N | N | N | N | N | N |
| Hydroquinone | 123-31-9 | Y | Y | Y | N | Y | Y |
| Potassium Carbonate | 584-08-7 | N | N | N | N | N | N |
| Potassium Hydroxide | 1310-58-3 | N | N | Y | N | N | N |
| Potassium Sulfite | 10117-38-1 | N | N | N | N | N | N |
| 3odium Sulfite | 7757-83-7 | N | N | N | N | N | N |
| Nater | 7732-18-5 | N | N | N | N | N | N |

FSCA 12(b) Export Notification CAS NUMBER CHEMICAL NAME

None Required

FOXICITY INFORMATION:

310540 - NAT-540 FINE LINE LIQUID DEVELOPER-I, 4 x 1 Gallon Fuji Hunt Photographic Chemicals, Inc.

Revised 11/24/09 Replaces 11/24/09 Printed 11/24/09

SECTION 15 - REGULATORY INFORMATION (Cont.)

IRC1 = IARC Group 1 Human Carcinogens List

IRC2 = IARC Group 2 Human Carcinogens List (limited human data)

IRC3 = IARC Group 2B Human Carcinogens List (sufficient animal data)

NTP = NTP Known Carcinogens List

DSHA = OSHA Known Carcinogens List

| Ingredients | CAS Number | IRC1 | IRC2 | IRC3 | NTP | OSHA |
|---------------------|------------|------|------|------|-----|------|
| Diethylene Glycol | 111-46-6 | N | N | N | N | N |
| Hydroquinone | 123-31-9 | N | N | N | N | N |
| Potassium Carbonate | 584-08-7 | N | N | N | N | N |
| Potassium Hydroxide | 1310-58-3 | N | N | N | N | N |
| Potassium Sulfite | 10117-38-1 | N | N | N | N | N |
| Godium Sulfite | 7757-83-7 | N | N | N | N | N |
| Nater | 7732-18-5 | N | N | N | N | N |

STATE REGULATIONS:

 ${
m FL}$ = Florida Hazardous Substance List MA = Massachusetts Right-To-Know List MI = Michigan Critical Materials List MN = Minnesota Hazardous Substance List

NJ = New Jersey Right-To-Know List PA = Pennsylvania Right-To-Know List

| Ingredients | CAS Number | PA | NJ | MN | MΙ | MA | FL |
|---------------------|------------|----|----|----|----|----|----|
| Diethylene Glycol | 111-46-6 | Y | N | Y | N | N | N |
| Hydroquinone | 123-31-9 | Y | Y | Y | Y | Y | Y |
| Potassium Carbonate | 584-08-7 | N | N | N | N | N | N |
| Potassium Hydroxide | 1310-58-3 | Y | Y | Y | N | Y | Y |
| Potassium Sulfite | 10117-38-1 | N | N | N | N | N | N |
| 3odium Sulfite | 7757-83-7 | N | N | N | N | N | N |
| Nater | 7732-18-5 | N | N | N | N | N | N |
| | | | | | | | |

The following designation is used only for those facilities that have air permits in nonattainment areas for ozone:

Non-Photochemically Reactive

SECTION 16 - OTHER INFORMATION

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.