

BlueSolar Charge Controllers MPPT 100/30 & 100/50

www.victronenergy.com

Ultrafast Maximum Power Point Tracking (MPPT)

Especially in case of a clouded sky, when light intensity is changing continuously, an ultra-fast MPPT controller will improve energy harvest by up to 30% compared to PWM charge controllers and by up to 10% compared to slower MPPT controllers.

Advanced Maximum Power Point Detection in case of partial shading conditions

If partial shading occurs, two or more maximum power points may be present on the power-voltage curve.

Conventional MPPTs tend to lock to a local MPP, which may not be the optimum MPP.

The innovative BlueSolar algorithm will always maximize energy harvest by locking to the optimum MPP.

Outstanding conversion efficiency

No cooling fan. Maximum efficiency exceeds 98%.

The full output current up to 40°C (104°F).

Flexible charge algorithm

Fully programmable charge algorithm (see the software page on our website), and eight pre-programmed algorithms, selectable with a rotary switch (see manual for details).

Extensive electronic protection

Over-temperature protection and power derating when temperature is high.

PV short circuit and PV reverse polarity protection.

PV reverse current protection.

Internal temperature sensor



Compensates absorption and float charge voltage for temperature.

Real-time data display options

- Apple and Android smartphones, tablets and other devices: see the VE.Direct to Bluetooth Smart dongle
- ColorControl panel



**Solar Charge Controller
MPPT 100/50**



Maximum Power Point Tracking

Upper curve:

Output current (I) of a solar panel as function of output voltage (V).

The Maximum Power Point (MPP) is the point Pmax along the curve where the product I x V reaches its peak.

Lower curve:

Output power $P = I \times V$ as function of output voltage.

When using a PWM (not MPPT) controller the output voltage of the solar panel will be nearly equal to the voltage of the battery, and will be lower than Vmp.

BlueSolar Charge Controller	MPPT 100/30		MPPT 100/50	
Battery voltage	12/24V Auto Select			
Rated charge current	30A		50A	
Nominal PV power, 12V 1a,b)	440W		700W	
Nominal PV power, 24V 1a,b)	880W		1400W	
Maximum PV open circuit voltage	100V		100V	
Max. PV short circuit current 2)	35A		60A	
Maximum efficiency	98%		98%	
Self-consumption	12V: 30 mA 24V: 20 mA			
Charge voltage 'absorption'	Default setting: 14,4V / 28,8V (adjustable)			
Charge voltage 'float'	Default setting: 13,8V / 27,6V (adjustable)			
Charge algorithm	multi-stage adaptive			
Temperature compensation	-16 mV / °C resp. -32 mV / °C			
Protection	Battery reverse polarity (fuse, not user accessible) PV reverse polarity Output short circuit Over temperature			
Operating temperature	-30 to +60°C (full rated output up to 40°C)			
Humidity	95%, non-condensing			
Data communication port	VE.Direct See the data communication white paper on our website			
ENCLOSURE				
Colour	Blue (RAL 5012)			
Power terminals	13 mm² / AWG6			
Protection category	IP43 (electronic components), IP22 (connection area)			
Weight	1,3 kg		1,3 kg	
Dimensions (h x w x d)	130 x 186 x 70 mm		130 x 186 x 70 mm	
STANDARDS				
Safety	EN/IEC 62109-1, UL 1741, CSA C22.2			
1a) If more PV power is connected, the controller will limit input power. 1b) PV voltage must exceed Vbat + 5V for the controller to start. Thereafter minimum PV voltage is Vbat + 1V. 2) A PV array with a higher short circuit current may damage the controller.				